



## CHALLENGER II Dry Blast Cabinet comes with an array of standard features.

- Constructed from high quality 2mm mild steel with a sturdy 4mm thick door front mounted as standard with safety inhibitor switch.
- Fully powder coated in grey or white
- 8ltr pressure pot system.
- Pressure regulator with gauge for fine adjustment to blasting pressure.
- 12 filter bag extractor unit with manual shaker for easy cleaning and low maintenance.
- Extractor is free standing as standard.
- Durable Boron carbide nozzle.
- Air blow off gun for a quick and easy clean.
- Anti-shadow LED lighting to give maximum illumination.
- The Challenger II requires a 16amp single phase power supply.

KEY: S = STANDARD FEATURES M/S = MILD STEEL

	<b>CHALLENGER II 1250</b>
<b>PRICE (NOK)</b>	<b>119.600,-</b>
<b>SPECIFICATIONS &amp; OPTIONS</b>	
INTERNAL DIMENSIONS (WIDTH x DEPTH x HEIGHT) (mm)	1250 x 1000 x 850
EXTERNAL DIMENSIONS (WIDTH x DEPTH x HEIGHT) (mm)	2050 x 1100 x 1950
<b>OPENINGS</b>	
FRONT SWING DOOR	S
<b>GAUNTLETS</b>	
HEAVY DUTY LINED GAUNTLETS	S
<b>RUBBER LINING</b>	
SINGLE REAR RUBBER LINED	2500,-
REAR AND BOTH SIDES RUBBER LINED	6800,-
FULLY RUBBER LINED	8000,-
<b>TURNTABLES</b>	
M/S ROTATING WHEEL STAND	3600,-
M/S TURNTABLE (MAX 80KG LOAD)	4700,-
<b>PRESSURE SYSTEM</b>	
8LTR PRESSURE POT	S

MORTEN AUTHEN AS – [www.ultralydvasker.no](http://www.ultralydvasker.no) - +47 911 69 826 – [post@ultralydvasker.no](mailto:post@ultralydvasker.no) – (PRISER ER EKSL.MVA OG FRAKT)

